
	PART NO:	DFN51120
	DRAWING NO:	DFN51120
	PAGE:	1 OF 2

<b>SPECIFICATION/SOURCE CONTROL DOCUMENT</b>				
<b>DESCRIPTION: RESISTOR, THERMAL FUSE 5.1ohm 250V 1.6W 5%</b>				
<u>N</u> SPECIFICATION CONTROL		<u>Y</u> SOURCE CONTROL		CERTIFICATION OF CONFORMANCE REQUIRED: ____
<u>Y</u> SAFETY AGENCY CONTROL	UL__Y__	CSA__Y__	VDE/TUV__Y__	RoHS__Y__
FIRST:	MANUFACTURER <b>UCHIHASHI</b>	MANUFACTURER PART NUMBER <b>A5MC-5R1J</b>		
SECOND:				
THIRD:				
UNIT OF MEASURE: <b>EACH</b>		PACKAGING: <b>RAIL</b>		

REV	DATE	ECO	ENG	ENG	SFTY	Q.A.	DESCRIPTION
A	8/18/09	91530	KR	PL	LD	A.S.	ORIGINAL RELEASE

ENGINEERING NOTES:  <b>Baan Code: 00122453</b>
LAMBDA CONFIDENTIAL



NEW PRODUCT

PbFree

## Thermal Cutoff/Resistor Assemblies A5MC

### ■ Ratings

Type Number	A5MC-5R1J	A5MC-6R8J	A5MC-100J	A5MC-150J	A5MC-220J
	L3.5	L3.5	L3.5	L3.5	L3.5
Nominal Resistance Value	5.1Ω	6.8Ω	10Ω	15Ω	22Ω
Resistance Tolerance	±5%				
Rated Functioning Temperature	139°C				
Rated Power	1.6W				
Maximum open circuit voltage	250 V AC				
Maximum open circuit voltage	70W				
Maximum overload power	UL C-UL VDE CCC				

### FEATURES

- A5MC is an environment-friendly product which does not contain cadmium and lead.

### IMPORTANT NOTICE

Read Standard Specification and Instruction Manual for use thoroughly.


### TERMS

- Rated Functioning Temperature (Tf)  
The acceptable tolerance is +0,-10°C except PSE. The one for PSE is 7°C

UL,C-UL:E50082, CSA: LR40743, VDE:923000-1171-0012

Cut-off temperature is measured with silicone oil bath of which temperature is increased at the rate of 1°C/min. Detecting current is 0.1A or less.  
Th and Tc are for C-UL(CSA) and CCC respectively.

### ■ Dimensions



寸 法 (mm)				
A	B	C	D	E
25.0±1.5	14.0±1.0	9.0±1.0	0.8±0.05	0.6±0.05
F	G	H	I	J
5.5±1.0	3.5 <sup>+0.5</sup> <sub>-0</sub>	3.5 <sup>+0.5</sup> <sub>-0</sub>	2.0±0.5	4.0±0.8

Uchihashi Estec Co.,Ltd.

- Head Quarters / Overseas Sales Section

9-14,Imazu-Kita 2-chome,Tsurumi-ku,Osaka 538-0041 Japan  
TEL (06)6962-6666(INT-81-6-6962-6666)  
FAX (06)6962-6668(INT-81-6-6962-6668)