



REV	DATE	BY	CHKD
A	9-18-13	CT	RL

- 1 CONNECTOR BODY AND COUPLING SLEEVE MATERIAL:
6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138
O-RING MATERIAL: FLUOROSILICONE PER SAE-AMS-R-25988
- $\triangle 2$ TERMINATED WITH MADISON CABLE 30 AWG 10G TURBO TWIN PAIR
- $\triangle 3$ CABLE LENGTH IS AS INDICATED IN THE CORRESPONDING NANONICS PART NUMBER
- $\triangle 4$ CAVITY POSITIONS ARE SHOWN FOR REFERENCE ONLY AND ARE NOT MARKED ON THE PART
- 5 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 6 REFERENCE TE PRODUCT SPECIFICATION 108-32048 FOR PRODUCT DETAILS AND PERFORMANCE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 31 JUL 2012	
DRAWN BY: M. STORRY	DATE: 31 JUL 12	NAME: M. STORRY	
CHECKED BY: M. STORRY	DATE: 31 JUL 12	PRODUCT SPEC: ---	PLUG ASSEMBLY, CIRCULAR, QUICK DISCONNECT W/ FLANGED COUPLING SLEEVE, METAL 8 POSITION, 10GbE, CeeLok FAS-T Nano Circular
DIMENSIONS: INCHES	UNLESS OTHERWISE SPECIFIED:	APPLICATION SPEC: ---	
0 P/LC ± .	1 P/LC ± .	2 P/LC ± .010	SIZE: A2
3 P/LC ± .005	4 P/LC ± .	5 P/LC ± .	CASE CODE: ---
6 P/LC ± .	7 P/LC ± .	8 P/LC ± .	DRAWING NO: 1925254
MATERIAL: ---	FINISH: ---	WEIGHT: ---	RESTRICTED TO: ---
SEE NOTES	SEE NOTES	CUSTOMER DRAWING	SCALE: G:1
			SHEET: 1 of 1
			REV: A