



REV	DATE	DESCRIPTION	BY	CHKD
A	9-18-13	PRODUCTION RELEASE PER ECO-13-014747	CT	RL

- 1 CONNECTOR BODY AND COUPLING SLEEVE MATERIAL:  
6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404  
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404  
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138  
O-RING MATERIAL: FLUOROSILICONE PER SAE-AMS-R-25988
- 2 TERMINATED WITH MADISON CABLE 30 AWG 10G TURBO TWIN PAIR
- 3 CABLE LENGTH IS AS INDICATED IN THE CORRESPONDING NANONICS PART NUMBER
- 4 CAVITY POSITIONS ARE SHOWN FOR REFERENCE ONLY AND ARE NOT MARKED ON THE PART
- 5 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 6 REFERENCE TE PRODUCT SPECIFICATION 108-32048 FOR PRODUCT DETAILS AND PERFORMANCE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 31 JUL 2012	
DRAWN BY: M. STORRY	DATE: 31 JUL 12	NAME: M. STORRY	
CHECKED BY: M. STORRY	DATE: 31 JUL 12	PRODUCT SPEC: PLUG ASSEMBLY, CIRCULAR, QUICK DISCONNECT	W/ FLANGED COUPLING SLEEVE, METAL, 8 POSITION, 10GbE, CeeLok FAS-T Nano Circular
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APPLICATION SPEC: A2	
0 P/LC ± .	1 P/LC ± .	WEIGHT: --	RESTRICTED TO: --
2 P/LC ± .010	3 P/LC ± .005	MATERIAL: --	SIZE: A2
4 P/LC ± .	ANGLES: ± 1°	FINISH: --	CASE CODE: OJPN9
MATERIAL: --	FINISH: --	SEE NOTES	DRAWING NO: 1925254
SEE NOTES	SEE NOTES	CUSTOMER DRAWING	SCALE: G:1
			SHEET: 1 of 1
			REV: A