



- 1 CONNECTOR BODY AND JAM NUT MATERIAL:
6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138
O-RING MATERIAL: FLUOROSILICONE PER SAE-AMS-R-25988
- 2 TERMINATED WITH MADISON CABLE 30 AWG 10G TURBO TWIN PAIR
- 3 CABLE LENGTH IS AS INDICATED IN THE CORRESPONDING NANONICS PART NUMBER
- 4 CAVITY POSITIONS ARE SHOWN FOR REFERENCE ONLY AND ARE NOT MARKED ON THE PART
- 5 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 6 REFERENCE TE PRODUCT SPECIFICATION 108-32048 FOR PRODUCT DETAILS AND PERFORMANCE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 31 JUL 2012	TE Connectivity	
DESIGNED BY: J. STORY	DATE: 31 JUL 2012	NAME: RECEPTACLE ASSEMBLY, CIRCULAR, REAR PANEL MOUNT, THREADED COUPLING/QUICK DISCONNECT, METAL, 8 POS, 10GbE, CeeLok FAS-T Nano Circular	SIZE: A2	CASE CODE: OPJN9
DRAWN BY: J. STORY	DATE: 31 JUL 2012	PRODUCT SPEC: A2	DRAWING NO: 1925258	RESTRICTED TO: A
APPROVED BY: M. STORY	DATE: 31 JUL 2012	APPLICATION SPEC: A2	WEIGHT: --	SCALE: G:1
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 P/LC ± .005	1 P/LC ± .010	2 P/LC ± .005
3 P/LC ± .005	4 P/LC ± .005	ANGLES: ± 1°	MATERIAL: SEE NOTES	
FINISH: SEE NOTES		CUSTOMER DRAWING		