

THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO. 16
HOTENDA TECHNOLOGY CO., LTD. IS A REGISTERED COMPANY IN THE PEOPLE'S REPUBLIC OF CHINA. ALL RIGHTS RESERVED. THIS DRAWING IS THE PROPERTY OF HOTENDA TECHNOLOGY CO., LTD. AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT PERMISSION IN WRITING FROM HOTENDA TECHNOLOGY CO., LTD., ALL RIGHTS ARE RESERVED.

USB ON

Part #	L (meters)	L (feet)	LC-Duplex Secure, Green		SC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1906073-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	-
0-1906073-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	-
0-1906073-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	-
0-1906073-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	-
0-1906073-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	-
0-1906073-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	-
0-1906073-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	-
0-1906073-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	-
0-1906073-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	-
1-1906073-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	-
1-1906073-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	-
1-1906073-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	-
1-1906073-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	-
1-1906073-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	-
1-1906073-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	-
1-1906073-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	-
1-1906073-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	-
1-1906073-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	-
1-1906073-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	-
2-1906073-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	-
2-1906073-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	-
2-1906073-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	-
2-1906073-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	-
2-1906073-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	-
2-1906073-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	-
2-1906073-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	-
2-1906073-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	-
2-1906073-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	-
2-1906073-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	-
3-1906073-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	-
3-1906073-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	-
3-1906073-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	-
3-1906073-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	-
3-1906073-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	-
3-1906073-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	-
3-1906073-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	-
3-1906073-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	-
3-1906073-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	-
3-1906073-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	-
4-1906073-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	-
4-1906073-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	-
4-1906073-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	-


Qty	U of M	Description	Item No.
2	piece	Trace Label	10
2	piece	CONN SUBASSY, MM, SC 1.6MM	9
4	piece	Eyelet/Shrink tube assembly - White	8
2	piece	SC Duplex Clip	7
AR	meter	2 Fiber, XG-50/125, 2.0mm, Twinzip, Aqua, OFNR (Riser)	6
2	piece	2.5mm ferrule cover	5
2	piece	SC Simplex Housing, Beige	4
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	3
1	piece	LC Duplex clip, black	2
2	piece	LC, SC, FC Straight Boot, Beige	1

THIS DRAWING IS A CONTROLLED DOCUMENT.

HOTENDA TECHNOLOGY CO.,LTD. IS THE SOLE PROPRIETOR OF THE INFORMATION CONTAINED HEREIN. THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED AND NOT SUBJECT TO EXPORT CONTROL. IT IS THE PROPERTY OF HOTENDA TECHNOLOGY CO.,LTD. AND IS TO BE KEPT CONFIDENTIAL. ANY UNAUTHORIZED DISCLOSURE OR REPRODUCTION IS STRICTLY PROHIBITED. CONTACT: SALES@HOTENDA.CN

LOC
CE
DIST
16

REV	DATE	BY	APPD	DESCRIPTION
A	20080914	JD		Rev Per ECN RELEASE
P				REVISION RECORD

RESTRICTED TO: 

UNLESS SPECIFIED OTHERWISE IN DIMENSIONS: METERS

1 P.C. : 1
 2 P.C. : 1
 3 P.C. : 1
 4 P.C. : 1

Cable Assy Configurator OR Jeremy Duncan APD Jeremy Duncan NAME: FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex Secure to SC-Duplex	MATERIAL: - HEAT TREAT: - AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608
SCALE: NTS SIZE: A2 DRAWING NO: C-1906073 SHEET: 2 of 4 REV: A	

CNC Customer Layout Rev: D

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---

USB 04

Part #	L (meters)	L (feet)	LC-Duplex Secure, Green		SC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1906073-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	-
4-1906073-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	-
4-1906073-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	-
4-1906073-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	-
4-1906073-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	-
4-1906073-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	-
4-1906073-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	-
5-1906073-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	-
5-1906073-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	-
5-1906073-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	-
5-1906073-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	-
5-1906073-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	-
5-1906073-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	-
5-1906073-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	-
5-1906073-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	-
5-1906073-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	-
5-1906073-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	-
6-1906073-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	-
6-1906073-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	-
6-1906073-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	-
6-1906073-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	-
6-1906073-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	-
6-1906073-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	-
6-1906073-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	-
6-1906073-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	-
6-1906073-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	-
6-1906073-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	-
7-1906073-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	-
7-1906073-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	-
7-1906073-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	-
7-1906073-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	-
7-1906073-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	-
7-1906073-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	-
7-1906073-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	-
7-1906073-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	-
7-1906073-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	-
7-1906073-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	-
8-1906073-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	-

THIS DRAWING IS A CONTROLLED DOCUMENT.

HOTENDA TECHNOLOGY CO.,LTD. IS THE SOLE PROPRIETOR OF THE RIGHTS IN THE PATENT RIGHTS AND TRADE MARKS OF THE COMPANY. ALL RIGHTS ARE RESERVED. THE COMPANY IS NOT RESPONSIBLE FOR THE CONTENTS OF THIS DOCUMENT. THE COMPANY IS NOT RESPONSIBLE FOR THE CONTENTS OF THIS DOCUMENT. THE COMPANY IS NOT RESPONSIBLE FOR THE CONTENTS OF THIS DOCUMENT.

LOC
CE
DIST
16

Rev Per ECR	RELEASE	3/14/2008	JD
P	LIB	REVISION RECORD	DATE

DIMENSIONS:
mm

DIMENSIONS UNITS:
OTHERWISE SPECIFIED

MPN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
DR	Jeremy Duncan				
APVD	Jeremy Duncan				
NMK	FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex Secure to SC-Duplex				
SCALE	NTS	SZS	AZ	DRAWING NO.	C-1906073
				SHEET	3 of 4
				REV	A

Restricted To:

USB 04

Label 1 Per specification 107-1645-1

Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin

This label is used on all lengths on this drawing.

Label 2 Per specification 107-1645-1

Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin

This label is used on all lengths on this drawing.

THIS DRAWING IS A CONTROLLED DOCUMENT.

ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED ARE IN MILLIMETERS. DIMENSIONS IN PARENTHESES ARE FOR INFORMATION ONLY. DIMENSIONS IN PARENTHESES ARE FOR INFORMATION ONLY. DIMENSIONS IN PARENTHESES ARE FOR INFORMATION ONLY. DIMENSIONS IN PARENTHESES ARE FOR INFORMATION ONLY.

LOC
CE
DIST
16

REV	DATE	BY	APP	DESCRIPTION
A	14/02/08	JD		Rev Per ECN RELEASE

DIMENSIONS:
 DIMENSIONS UNLESS OTHERWISE SPECIFIED:
 0 P.L.C
 1 P.L.C
 2 P.L.C
 3 P.L.C
 4 P.L.C

MPN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
DR	Jeremy Duncan				
APVD	Jeremy Duncan				
NAME		FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex Secure to SC-Duplex			
SCALE	NTS	SZS	AZ	DRAWING NO	C-1906073
				SHEET	4 of 4
				REV	A

Restricted To:

8 | 7 | 6 | 5 | 4 | 3 | 2 | 1