



308 Constitution Drive
Menlo Park, CA 94025-1164
Phone: 800-227-4856
www.circuitprotection.com

PolySwitch®
PTC Devices
Overcurrent Protection Device

PRODUCT: TS600-200F-RA-B-0.5

DOCUMENT: SCD26005
PCN: F02483-000
REV LETTER: D
REV DATE: MAY 10, 2011
PAGE NO.: 1 OF 1

Specification Status: RELEASED

Max Electrical Rating at 20°C

Operating Voltage: **60V_{DC}**
Interrupt Current: **3A_{RMS}**

Fault Voltage: **600V_{RMS}**

Terminal Material: Tin plated brass
Case Material: 1000 V Dielectric rating
Marking:

- Raychem Logo
- T20 Part Identification
- Lot Identification




TABLE I. DIMENSIONS:

	A		B		C		D		E		F	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
mm:	18.29	19.43	11.56	12.32	7.24	8.26	1.65	2.41	9.91	10.41	1.52	2.29
in*:	(0.720)	(0.765)	(0.455)	(0.485)	(0.285)	(0.325)	(0.065)	(0.095)	(0.390)	(0.410)	(0.060)	(0.090)

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS @ 20°C (unless otherwise noted):

I _{HOLD} (A)		RESISTANCE (Ω)				TIME TO TRIP(s) @ 1A TYP	OPERATING Temperature (°C)		Power Dissipation Watts, Typical
20°C	70°C	R MIN	R MAX	R _{1Inst} *	R _{1 MAX} **		MIN	MAX	
0.200	0.110	4.0	7.5	13.5	13.5	12	-40	85	2.5

*Post Reflow Resistance, measured after one hour.

**Maximum device resistance at 20°C measured 1 hour post trip.

Resistance Matched 0.5 Ohm

- Agency Recognitions: CSA, UL Recognition file #E74889
- Reference Documents: PS300
- Precedence: This specification takes precedence over documents referenced herein.
- Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.
- CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

ROHS Compliant

ELV Compliant

Pb-Free

Directive 2002/95/EC
Compliant

Directive 2000/53/EC
Compliant

