

HARTING PushPull



Identification	Part No.	Drawing	Dimensions in mm
----------------	----------	---------	------------------

<p>Fibre optic cable, double ended, multi mode, 62.5 µm</p> <p>Length: a = 1 m</p> <p>a = 5 m</p> <p>a = 10 m</p> <p>a = 20 m</p> <p>a = 40 m</p> <p>a = 50 m</p> <p>a = 100 m</p>	<p>33 58 211 0010 001</p> <p>33 58 211 0050 001</p> <p>33 58 211 0100 001</p> <p>33 58 211 0200 001</p> <p>33 58 211 0400 001</p> <p>33 58 211 0500 001</p> <p>33 58 211 1000 001</p>	<p>double ended</p> <p>Protection level: IP 65 / IP 67</p> <p>single ended</p>
<p>Fibre optic cable, single ended, multi mode, 62.5 µm</p> <p>Length: a = 1 m</p> <p>a = 5 m</p> <p>a = 10 m</p> <p>a = 20 m</p> <p>a = 40 m</p> <p>a = 50 m</p> <p>a = 100 m</p>	<p>33 58 111 0010 001</p> <p>33 58 111 0050 001</p> <p>33 58 111 0100 001</p> <p>33 58 111 0200 001</p> <p>33 58 111 0400 001</p> <p>33 58 111 0500 001</p> <p>33 58 111 1000 001</p>	<p>Protection level: IP 65 / IP 67</p> <p>single ended</p>

<p>Fibre optic breakout cable, multi mode, 62.5 µm</p> <p>Length: 10 m</p> <p>Length: 20 m</p> <p>Length: 100 m</p>	<p>33 58 751 0100 001</p> <p>33 58 751 0200 001</p> <p>33 58 751 1000 001</p>	<p>PUR jacket</p> <p>2-fibre multi mode 62.5 µm</p> <p>Outer diameter: 7 mm</p> <p>Min. bending radius: Installation: 10.5 cm Operating: 7.0 cm</p>
---	---	---